

Fast,
small &
incredible control



		Nr of control channels	Supply voltage range (V)	Maximum power output (W)	Maximum load (A)	Onboard current settings (mA)	External current setting (mA)	Reverse polarity protection	NTC interface	DMX / LedSync in	LedSync out	LedSync thru	Connection	DIN rail fitting	Dimensions in mm (LxW or Ø)
L Series															
L-Dot Standard															
L-Dot/S 1055	LDS10552	1	24-32	50	-	350/460/700/900/1100/1200	350-1500	-	✓	✓	✓	-	pad	-	Ø40
L-Dot/S 2055	LDS20552	2	24-32	50	-	350/460/700/900/1100/1200	350-1500	-	✓	✓	✓	-	pad	-	Ø40
L-Dot/S 3055	LDS30552	3	24-32	50	-	350/460/700/900/1100/1200	350-1500	-	✓	✓	✓	-	pad	-	Ø40
L-Dot/S 4055	LDS40552	4	24-32	50	-	350/460/700/900/1100/1200	350-1500	-	✓	✓	✓	-	pad	-	Ø40
L-Dot Connector															
L-Dot/C 1055	LDC10552	1	24-32	50	-	350/460/700/900/1100/1200	350-1500	✓	✓	✓	✓	-	screw	✓	68x50
L-Dot/C 2055	LDC20552	2	24-32	50	-	350/460/700/900/1100/1200	350-1500	✓	✓	✓	✓	-	screw	✓	68x50
L-Dot/C 3055	LDC30552	3	24-32	50	-	350/460/700/900/1100/1200	350-1500	✓	✓	✓	✓	-	screw	✓	68x50
L-Dot/C 4055	LDC40552	4	24-32	50	-	350/460/700/900/1100/1200	350-1500	✓	✓	✓	✓	-	screw	✓	68x50
L-Dot Nano															
L-Dot/N 1025	LDN10252	1	24-28	30	-	350	350-1000	-	✓	✓	-	-	pad	-	Ø30
L-Dot/N 2025	LDN20252	2	24-28	30	-	350	350-1000	-	✓	✓	-	-	pad	-	Ø30
L-Dot/N 3025	LDN30252	3	24-28	30	-	350	350-1000	-	✓	✓	-	-	pad	-	Ø30
L-Dot/N 4025	LDN40252	4	24-28	30	-	350	350-1000	-	✓	✓	-	-	pad	-	Ø30
L-Dot Pico															
L-Dot/P 1015	LDP10151	1	12-28	15	-	350	350-700	-	✓	✓	-	-	pad	-	Ø25
L-Dot/P 2015	LDP20151	2	12-28	15	-	350	350-700	-	✓	✓	-	-	pad	-	Ø25
L-Dot/P 3015	LDP30151	3	12-28	15	-	350	350-700	-	✓	✓	-	-	pad	-	Ø25
L-Dot/P 4015	LDP40151	4	12-28	15	-	350	350-700	-	✓	✓	-	-	pad	-	Ø25
L-Strip Standard															
L-Strip/S 1025	LSS10251	1	24-28	20	-	350	350-700	-	✓	✓	✓	-	pin	-	34x24
L-Strip/S 2025	LSS20251	2	24-28	20	-	350	350-700	-	✓	✓	✓	-	pin	-	34x24
L-Strip/S 3025	LSS30251	3	24-28	20	-	350	350-700	-	✓	✓	✓	-	pin	-	34x24
L-Strip/S 4025	LSS40251	4	24-28	20	-	350	350-700	-	✓	✓	✓	-	pin	-	34x24
L-Strip Connector															
L-Strip/C 1025	LSC10252	1	24-28	30	-	350/460/700/900	350-1000	✓	✓	✓	✓	-	screw	-	105x24
L-Strip/C 2025	LSC20252	2	24-28	30	-	350/460/700/900	350-1000	✓	✓	✓	✓	-	screw	-	105x24
L-Strip/C 3025	LSC30252	3	24-28	30	-	350/460/700/900	350-1000	✓	✓	✓	✓	-	screw	-	105x24
L-Strip/C 4025	LSC40252	4	24-28	30	-	350/460/700/900	350-1000	✓	✓	✓	✓	-	screw	-	105x24

			Nr of control channels	Supply voltage range (V)	Maximum power output (W)	Maximum load (A)	Onboard current settings (mA)	External current setting (mA)	Reverse polarity protection	NTC interface	DMX / LedSync in	LedSync out	LedSync thru	Connection	DIN rail fitting	Dimensions in mm (LxW or ø)
LM Series																
LM-Dot Standard																
LM-Dot/S 3155	LMS31551	3	24-32	150	-	350/700/1000/1400	-	✓	✓	✓	✓	-	pad	✓	92x50	
LM-Dot/S 4155	LMS41551	4	24-32	150	-	350/700/1000/1400	-	✓	✓	✓	✓	-	pad	✓	92x50	
LM-Dot Connector																
LM-Dot/C 3155	LMC31551	3	24-32	150	-	350/700/1000/1400	-	✓	✓	✓	✓	-	screw	✓	92x50	
LM-Dot/C 4155	LMC41551	4	24-32	150	-	350/700/1000/1400	-	✓	✓	✓	✓	-	screw	✓	92x50	
LM-Dot Pico																
LM-Dot/P 3045	LMP30451	3	24-32	40	-	350/700	-	✓	✓	✓	✓	-	screw	✓	68x50	
LM-Dot/P 4055	LMP40551	4	24-32	50	-	350/700	-	✓	✓	✓	✓	-	screw	✓	68x50	
V Series																
V-Strip Standalone																
V-Strip/S 4040	VSS40401	4	12-28	-	4	-	-	-	-	-	-	-	pad	-	40x17	
V-Strip Network																
V-Strip/N 4045	VSN40451	4	12-28	-	8	-	-	✓	-	✓	✓	-	screw	✓	68x50	
V-Strip Power																
V-Strip/P 4045	VSP40451	4	12-28	-	32	-	-	✓	-	✓	✓	-	screw	✓	68x50	