

NAMING	DIM		DRIVE											NETWORKING					CONTROL		CERTIFICATION	LOOK and FEEL					STATUS			
			Name	Commercial order number	Dimming down to	Dim Curves	Type Constant Current/Voltage	Output Power	# LED outputs	V input	Available V _I	Max output current	Output current resolution	Output voltage	Max output load in total	Max output load per output group	Auxiliary output	0-10V	DMX	RDM	Buffered DMX (LED SYNC)	DALI	LEDcode	# DMX addresses	# DALI addresses (ballasts)	Certification		Display	Cable retention	Form-factor
constant current																														
ECODrive 361/S, 0-10V	EC0361S2	1%	LIN, LOG	cc	30W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	25mA	n.a.	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, TL-Type, RCM			brick, side feed	metal	130 x 72 x 35mm	X
ECODrive 361/B, 0-10V	EC0361B2	1%	LIN, LOG	cc	30W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	25mA	n.a.	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, TL-Type, RCM			brick, bottom feed	metal	130 x 72 x 35mm	X
ECODrive 361/A, 0-10V	EC0361A3	1%	LIN, LOG	cc	30W	1	120-277VAC	(2 - 55V)	(150 - 1050mA)	25mA	n.a.	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, RCM	X		stick, side feed	plastic	210 x 41 x 34 mm	X
ECODrive 361/M, 0-10V	EC0361M1	1%	LIN, LOG	cc	30W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	25mA	n.a.	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	UL			stick, side feed	metal	240 x 42 x 30 mm	X
ECODrive 366/M, 0-10V + AUX	EC0366M1	1%	LIN, LOG	cc	30W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	25mA	n.a.	n.a.	n.a.	15 - 25.5V / 18mA max	n.a.	X					X	n.a.	n.a.	UL			stick, side feed	metal	240 x 42 x 30 mm	X
ECODrive 366/L, 0-10V + AUX	EC0366L2	1%	LIN, LOG	cc	30W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	25mA	n.a.	n.a.	n.a.	15 - 25.5V / 18mA max	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, TL-Type			stick, side feed	metal	320 x 30 x 26 mm	X
ECODrive 360/S, DALI	EC0360S2	1%	LIN, LOG	cc	30W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	25mA	n.a.	n.a.	n.a.	n.a.	n.a.					X	X	n.a.	1	CE, ENEC, UL, TL-Type, RCM			brick, side feed	metal	130 x 72 x 35mm	X
ECODrive 360/B, DALI	EC0360B2	1%	LIN, LOG	cc	30W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	25mA	n.a.	n.a.	n.a.	n.a.	n.a.					X	X	n.a.	1	CE, ENEC, UL, TL-Type, RCM			brick, bottom feed	metal	130 x 72 x 35mm	X
ECODrive 360/A, DALI	EC0360A3	1%	LIN, LOG	cc	30W	1	120-277VAC	(2 - 55V)	(150 - 1050mA)	25mA	n.a.	n.a.	n.a.	n.a.	n.a.					X	X	n.a.	1	CE, ENEC, UL, RCM	X		stick, side feed	plastic	210 x 41 x 34 mm	X
ECODrive 365/L, DALI + AUX	EC0365L2	1%	LIN, LOG	cc	30W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	25mA	n.a.	n.a.	n.a.	15 - 25.5V / 18mA max	n.a.					X	X	n.a.	1	CE, ENEC, UL, TL-Type			stick, side feed	metal	320 x 30 x 26 mm	X
SOLDrive 361/S, 0-10V	SL0361S2	0,1%	LIN, SOFT-LIN, SQU, LOG	cc	30W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	1mA	n.a.	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, TL-Type, RCM			brick, side feed	metal	130 x 72 x 35mm	X
SOLDrive 361/B, 0-10V	SL0361B2	0,1%	LIN, SOFT-LIN, SQU, LOG	cc	30W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	1mA	n.a.	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, TL-Type, RCM			brick, bottom feed	metal	130 x 72 x 35mm	X
SOLDrive 361/A, 0-10V	SL0361A3	0,1%	LIN, SOFT-LIN, SQU, LOG	cc	30W	1	120-277VAC	(2 - 55V)	(150 - 1050mA)	1mA	n.a.	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, RCM	X		stick, side feed	plastic	210 x 41 x 34 mm	X
SOLDrive 366/L, 0-10V + AUX	SL0366L2	0,1%	LIN, SOFT-LIN, SQU, LOG	cc	30W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	1mA	n.a.	n.a.	n.a.	15 - 25.5V / 18mA max	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, TL-Type			stick, side feed	metal	320 x 30 x 26 mm	X
SOLDrive 360/S, DALI	SL0360S2	0,1%	LIN, LOG	cc	30W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	1mA	n.a.	n.a.	n.a.	n.a.	n.a.					X	X	n.a.	1	CE, ENEC, UL, TL-Type, RCM			brick, side feed	metal	130 x 72 x 35mm	X
SOLDrive 360/B, DALI	SL0360B2	0,1%	LIN, LOG	cc	30W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	1mA	n.a.	n.a.	n.a.	n.a.	n.a.					X	X	n.a.	1	CE, ENEC, UL, TL-Type, RCM			brick, bottom feed	metal	130 x 72 x 35mm	X
SOLDrive 360/A, DALI	SL0360A3	0,1%	LIN, LOG	cc	30W	1	120-277VAC	(2 - 55V)	(150 - 1050mA)	1mA	n.a.	n.a.	n.a.	n.a.	n.a.					X	X	n.a.	1	CE, ENEC, UL, RCM	X		stick, side feed	plastic	210 x 41 x 34 mm	X
SOLDrive 365/L, DALI + AUX	SL0365L2	0,1%	LIN, LOG	cc	30W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	1mA	n.a.	n.a.	n.a.	15 - 25.5V / 18mA max	n.a.					X	X	n.a.	1	CE, ENEC, UL, TL-Type			stick, side feed	metal	320 x 30 x 26 mm	X
ECODrive 561/S, 0-10V	EC0561S2	1%	LIN, LOG	cc	50W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	25mA	n.a.	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, TL-Type			brick, side feed	metal	130 x 76 x 30 mm	X
ECODrive 561/B, 0-10V	EC0561B2	1%	LIN, LOG	cc	50W	1	120-277VAC	(2 - 55V)	(150 - 900mA)	25mA	n.a.	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	UL, TL-Type			brick, bottom feed	metal	130 x 72 x 35mm	X
ECODrive 561/B, 0-10V	EC0561B2	1%	LIN, LOG	cc	50W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	25mA	n.a.	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	UL, TL-Type			brick, bottom feed	metal	130 x 72 x 35mm	X
ECODrive 561/A, 0-10V	EC0561A2	1%	LIN, LOG	cc	50W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	25mA	n.a.	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, TL-Type	X		brick, side feed	plastic	153 x 76 x 31 mm	X
ECODrive 561/M, 0-10V	EC0561M2	1%	LIN, LOG	cc	50W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	25mA	n.a.	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	UL			stick, side feed	metal	240 x 42 x 30 mm	X
ECODrive 566/M, 0-10V + AUX	EC0566M2	1%	LIN, LOG	cc	50W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	25mA	n.a.	n.a.	n.a.	15 - 25.5V / 18mA max	n.a.	X					X	n.a.	n.a.	UL			stick, side feed	metal	240 x 42 x 30 mm	X
ECODrive 566/U, 0-10V + AUX	EC0566U1	1%	LIN, LOG	cc	50W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	25mA	n.a.	n.a.	n.a.	15 - 25.5V / 18mA max	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, TL-Type			stick, side feed	metal	444 x 30 x 21 mm	X
ECODrive 566/L, 0-10V + AUX	EC0566L2	1%	LIN, LOG	cc	50W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	25mA	n.a.	n.a.	n.a.	15 - 25.5V / 18mA max	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, TL-Type			stick, side feed	metal	320 x 30 x 26 mm	X
ECODrive 560/S, DALI	EC0560S2	1%	LIN, LOG	cc	50W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	25mA	n.a.	n.a.	n.a.	n.a.	n.a.					X	X	n.a.	1	CE, ENEC, UL, TL-Type			brick, side feed	metal	130 x 76 x 30 mm	X
ECODrive 560/B, DALI	EC0560B1	1%	LIN, LOG	cc	50W	1	120-277VAC	(2 - 55V)	(150 - 900mA)	25mA	n.a.	n.a.	n.a.	n.a.	n.a.					X	X	n.a.	1	UL, TL-Type			brick, bottom feed	metal	130 x 72 x 35mm	X
ECODrive 560/B, DALI	EC0560B2	1%	LIN, LOG	cc	50W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	25mA	n.a.	n.a.	n.a.	n.a.	n.a.					X	X	n.a.	1	UL, TL-Type			brick, bottom feed	metal	130 x 72 x 35mm	X
ECODrive 560/A, DALI	EC0560A2	1%	LIN, LOG	cc	50W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	25mA	n.a.	n.a.	n.a.	n.a.	n.a.					X	X	n.a.	1	CE, ENEC, UL, TL-Type	X		brick, side feed	plastic	153 x 76 x 31 mm	X
ECODrive 565/U, DALI + AUX	EC0565U1	1%	LIN, LOG	cc	50W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	25mA	n.a.	n.a.	n.a.	15 - 25.5V / 18mA max	n.a.					X	X	n.a.	1	CE, ENEC, UL, TL-Type			stick, side feed	metal	444 x 30 x 21 mm	X
ECODrive 565/L, DALI + AUX	EC0565L2	1%	LIN, LOG	cc	50W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	25mA	n.a.	n.a.	n.a.	15 - 25.5V / 18mA max	n.a.					X	X	n.a.	1	CE, ENEC, UL, TL-Type			stick, side feed	metal	320 x 30 x 26 mm	X
SOLDrive 561/S, 0-10V	SL0561S2	0,1%	LIN, LOG	cc	50W	2	120-277VAC	2 x (2 - 55V)	2 x (200 - 1050mA)	1mA	n.a.	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, RCM			brick, side feed	metal	130 x 76 x 30 mm	X
SOLDrive 561/S, 0-10V	SL0561S3	0,1%	LIN, SOFT-LIN, SQU, LOG	cc	50W	2	120-277VAC	2 x (2 - 55V)	2 x (150 - 1400mA)	1mA	n.a.	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, TL-Type			brick, side feed	metal	130 x 76 x 30 mm	X
SOLDrive 564/S, 0-10V	SL0564S2	0,1%	LIN, SOFT-LIN, SQU, LOG	cc	50W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	1mA	n.a.	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, TL-Type, RCM			brick, side feed	metal	130 x 76 x 30 mm	X
SOLDrive 564/B, 0-10V	SL0564B1	0,1%	LIN, SOFT-LIN, SQU, LOG	cc	50W	1	120-277VAC	(2 - 55V)	(150 - 900mA)	1mA	n.a.	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	UL, TL-Type			brick, bottom feed	metal	130 x 72 x 35mm	X
SOLDrive 564/B, 0-10V	SL0564B2	0,1%	LIN, SOFT-LIN, SQU, LOG	cc	50W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	1mA	n.a.	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	UL, TL-Type			brick, bottom feed	metal	130 x 72 x 35mm	X
SOLDrive 561/A, 0-10V	SL0561A2	0,1%	LIN, LOG	cc	50W	2	120-277VAC	2 x (2 - 55V)	2 x (200 - 1050mA)	1mA	n.a.	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, TL-Type, RCM	X		brick, side feed	plastic	153 x 76 x 31 mm	X
SOLDrive 561/M, 0-10V	SL0561M2	0,1%	LIN, LOG	cc	50W	2	120-277VAC	2 x (2 - 55V)	2 x (200 - 1050mA)	1mA	n.a.	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, RCM			stick, side feed	metal	444 x 30 x 21 mm	X
SOLDrive 561/U, 0-10V	SL0561U1	0,1%	LIN, SOFT-LIN, SQU, LOG	cc	50W	2	120-277VAC	2 x (2 - 55V)	2 x (150 - 1400mA)	1mA	n.a.	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, TL-Type			stick, side feed	metal	444 x 30 x 21 mm	X
SOLDrive 566/U, 0-10V + AUX	SL0566U1	0,1%	LIN, SOFT-LIN, SQU, LOG	cc	50W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)	1mA	n.a.	n.a.	n.a.	15 - 25.5V / 18mA max	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, TL-Type			stick, side feed	metal	444 x 30 x 21 mm	X
SOLDrive 566/L, 0-10V + AUX	SL0566L2	0,1%	LIN, SOFT-LIN, SQU, LOG	cc	50W	1	120-277VAC	(2 - 55V)	(150 - 1400mA)																					

	NAMING		DIM		DRIVE										NETWORKING					CONTROL		CERTIFICATION	LOOK and FEEL				STATUS			
	Name	Commercial order number	Dimming down to	Dim Curves	Type Constant Current/Voltage	Output Power	# LED outputs	V input	Available Vf	Max output current	Output current resolution	Output voltage	Max output load in total	Max output load per output group	Auxiliary output	0-10V	DMX	RDM	Buffered DMX (LED SYNC)	DALI	LEDcode	# DMX addresses	# DALI addresses (ballasts)	Certification	Display	Cable retention	Form-factor	Material	Size	In production
AC	ECOdrive 1066/M, 0-10V + AUX	EC1066M1	1%	LIN, LOG	cc	100W	2	120-277VAC	2 x (2 - 55V)	2 x (150 - 1400mA)	25mA	n.a.	n.a.	n.a.	15 - 25.5V / 18mA max	X					X	n.a.	n.a.	CE, ENEC, UL, TL-Type			brick, side feed	metal	230 x 80 x 30 mm	
	ECOdrive 1065/S, DALI + AUX	EC1065S1	1%	LIN, LOG	cc	100W	2	120-277VAC	2 x (2 - 55V)	2 x (150 - 1400mA)	25mA	n.a.	n.a.	n.a.	15 - 25.5V / 18mA max					X	X	n.a.	1	CE, ENEC, UL, TL-Type			brick, side feed	metal	230 x 80 x 30 mm	
	ECOdrive 1065/M, DALI + AUX	EC1065M1	1%	LIN, LOG	cc	100W	2	120-277VAC	2 x (2 - 55V)	2 x (150 - 1400mA)	25mA	n.a.	n.a.	n.a.	15 - 25.5V / 18mA max					X	X	n.a.	1	CE, ENEC, UL, TL-Type			stick, side feed	metal	370 x 41 x 30 mm	
	SOLOdrive 1061/S, 0-10V	SL1061S1	0,1%	LIN, LOG	cc	100W	4	120-277VAC	4 x (2 - 57V)	4 x (200 - 1050mA)	1mA	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, RCM			brick, side feed	metal	230 x 80 x 30 mm	X
	SOLOdrive 1061/A, 0-10V	SL1061A1	0,1%	LIN, LOG	cc	100W	4	120-277VAC	4 x (2 - 57V)	4 x (200 - 1050mA)	1mA	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, RCM	X		stick, side feed	plastic	388 x 42 x 30mm	X
	SOLOdrive 1061/M, 0-10V	SL1061M1	0,1%	LIN, LOG	cc	100W	4	120-277VAC	4 x (2 - 57V)	4 x (200 - 1050mA)	1mA	n.a.	n.a.	n.a.	n.a.	X					X	n.a.	n.a.	CE, ENEC, UL, RCM			stick, side feed	metal	370 x 41 x 30 mm	X
	SOLOdrive 1060/S, DALI	SL1060S1	0,1%	LIN, LOG	cc	100W	4	120-277VAC	4 x (2 - 57V)	4 x (200 - 1050mA)	1mA	n.a.	n.a.	n.a.	n.a.					X	X	n.a.	1	CE, ENEC, UL, RCM			brick, side feed	metal	230 x 80 x 30 mm	X
	SOLOdrive 1060/A, DALI	SL1060A1	0,1%	LIN, LOG	cc	100W	4	120-277VAC	4 x (2 - 57V)	4 x (200 - 1050mA)	1mA	n.a.	n.a.	n.a.	n.a.					X	X	n.a.	1	CE, ENEC, UL, RCM	X		stick, side feed	plastic	388 x 42 x 30mm	X
	SOLOdrive 1060/M, DALI	SL1060M1	0,1%	LIN, LOG	cc	100W	4	120-277VAC	4 x (2 - 57V)	4 x (200 - 1050mA)	1mA	n.a.	n.a.	n.a.	n.a.					X	X	n.a.	1	CE, ENEC, UL, RCM			stick, side feed	metal	370 x 41 x 30 mm	X
	DUALdrive 1060/S, DALI	DL1060S1	0,1%	LIN, LOG	cc	100W	4	120-277VAC	4 x (2 - 57V)	4 x (200 - 1050mA)	1mA	n.a.	n.a.	n.a.	n.a.					X	X	n.a.	2	CE, ENEC, UL, RCM			brick, side feed	metal	230 x 80 x 30 mm	X
	DUALdrive 1060/A, DALI	DL1060A1	0,1%	LIN, LOG	cc	100W	4	120-277VAC	4 x (2 - 57V)	4 x (200 - 1050mA)	1mA	n.a.	n.a.	n.a.	n.a.					X	X	n.a.	2	CE, ENEC, UL, RCM	X		stick, side feed	plastic	388 x 42 x 30mm	X
	DUALdrive 1060/M, DALI	DL1060M1	0,1%	LIN, LOG	cc	100W	4	120-277VAC	4 x (2 - 57V)	4 x (200 - 1050mA)	1mA	n.a.	n.a.	n.a.	n.a.					X	X	n.a.	2	CE, ENEC, UL, RCM			stick, side feed	metal	370 x 41 x 30 mm	X
	POWERdrive 1061/S, DMX	PW1061S1	0,1%	LIN, SQU, LOG	cc	100W	4	120-277VAC	4 x (2 - 57V)	4 x (200 - 1050mA)	10mA	n.a.	n.a.	n.a.	n.a.		X	X	X			1-4	n.a.	CE, ENEC, UL			brick, side feed	metal	230 x 80 x 30 mm	X
	POWERdrive 1061/M, DMX	PW1061M1	0,1%	LIN, SQU, LOG	cc	100W	4	120-277VAC	4 x (2 - 57V)	4 x (200 - 1050mA)	10mA	n.a.	n.a.	n.a.	n.a.		X	X	X			1-4	n.a.	CE, ENEC, UL			stick, side feed	metal	370 x 41 x 30 mm	X
	POWERdrive 106/S, DMX/DALI	PWR106S1	0,1%	LIN, LOG	cc	100W	4	120-277VAC	4 x (2 - 57V)	4 x (200 - 1050mA)	50mA @ display 10mA @ FluxTool	n.a.	n.a.	n.a.	n.a.		X	X	X	X		1-4	1-4	CE, ENEC, UL, RCM	X		brick, side feed	metal	230 x 80 x 30 mm	X
POWERdrive 1060/A, DMX/DALI	PWR1060A1	0,1%	LIN, LOG	cc	100W	4	120-277VAC	4 x (2 - 57V)	4 x (200 - 1050mA)	50mA @ display 10mA @ FluxTool	n.a.	n.a.	n.a.	n.a.		X	X	X	X		1-4	1-4	CE, ENEC, UL, RCM	X	X	stick, side feed	plastic	388 x 42 x 30mm	X	
POWERdrive 106/M, DMX/DALI	PWR106M1	0,1%	LIN, LOG	cc	100W	4	120-277VAC	4 x (2 - 57V)	4 x (200 - 1050mA)	50mA @ display 10mA @ FluxTool	n.a.	n.a.	n.a.	n.a.		X	X	X	X		1-4	1-4	CE, ENEC, UL, RCM	X		stick, side feed	metal	370 x 41 x 30 mm	X	
POWERdrive 6060/R, DMX/DALI/0-1	PW6060R1	0,1%	LIN, SQU, LOG	cc	600W	32	120-240VAC	32 x (5 - 48V)	32 x (200 - 1050mA)	50mA @ display	n.a.	n.a.	n.a.	n.a.		X	X	X	X		1-32	1-4	CE, UL	X		19" rackmount, 1U	metal	428 x 329 x 45 mm	X	
constant voltage																														
LINEARdrive 100/S, DMX/DALI	LIN100S1	0,1%	LIN, LOG	cv	100W	4	120-277VAC	n.a.	n.a.	n.a.	12 / 24V	8A / 4A	2.8 A	n.a.		X	X	X	X		1-4	1-4	CE, ENEC, UL, RCM	X		brick, side feed	metal	230 x 80 x 30 mm	X	
LINEARdrive 100/A, DMX/DALI	LIN100A1	0,1%	LIN, LOG	cv	100W	4	120-277VAC	n.a.	n.a.	n.a.	12 / 24V	8A / 4A	2.8 A	n.a.		X	X	X	X		1-4	1-4	CE, ENEC, UL, RCM	X	X	stick, side feed	plastic	388 x 42 x 30mm	X	
LINEARdrive 100/M, DMX/DALI	LIN100M1	0,1%	LIN, LOG	cv	100W	4	120-277VAC	n.a.	n.a.	n.a.	12 / 24V	8A / 4A	2.8 A	n.a.		X	X	X	X		1-4	1-4	CE, ENEC, UL, RCM	X		stick, side feed	metal	370 x 41 x 30 mm	X	
constant current																														
ECOdrive 15/D, DMX	ECO015D1	0,1%	LIN, LOG	cc	15W	4	12/24/32VDC	(V input -1V)	200 - 500mA	50mA @ display	n.a.	n.a.	n.a.	n.a.		X					1-4	n.a.	CE, UL	X	X	stick, side feed	plastic	153 x 50 x 23 mm	X	
ECOdrive 30/D, DMX	ECO030D1	0,1%	LIN, LOG	cc	30W	4	12/24/32VDC	(V input -1V)	200 - 1050mA	50mA @ display	n.a.	n.a.	n.a.	n.a.		X					1-4	n.a.	CE, UL	X	X	stick, side feed	plastic	153 x 50 x 23 mm	X	
ECOdrive 45/D, DMX	ECO045D1	0,1%	LIN, LOG	cc	45W	4	12/24/32VDC	(V input -1V)	200 - 1400mA	50mA @ display	n.a.	n.a.	n.a.	n.a.		X					1-4	n.a.	CE, UL	X	X	stick, side feed	plastic	153 x 50 x 23 mm	X	
POWERdrive 45/D, DMX/DALI	PWR045D1	0,1%	LIN, LOG	cc	45W	4	12/24/32VDC	4 x (V input - 1V)	4 x (200 - 500mA)	50mA @ display	n.a.	n.a.	n.a.	n.a.		X	X	X	X		1-4	1-4	CE, UL	X	X	stick, side feed	plastic	193 x 50 x 23 mm	X	
POWERdrive 90/D, DMX/DALI	PWR090D1	0,1%	LIN, LOG	cc	90W	4	12/24/32VDC	4 x (V input - 1V)	4 x (200 - 1050mA)	50mA @ display	n.a.	n.a.	n.a.	n.a.		X	X	X	X		1-4	1-4	CE, UL	X	X	stick, side feed	plastic	193 x 50 x 23 mm	X	
POWERdrive 180/D, DMX/DALI	PWR180D1	0,1%	LIN, LOG	cc	180W	4	12/24/32VDC	4 x (V input - 1V)	4 x (200 - 1400mA)	50mA @ display	n.a.	n.a.	n.a.	n.a.		X	X	X	X		1-4	1-4	CE, UL	X	X	stick, side feed	plastic	193 x 50 x 23 mm	X	
constant voltage																														
LINEARdrive 180/D, DMX	LIN180D3	0,1%	LIN, LOG	cv	180W	4	12/24/28VDC	n.a.	n.a.	n.a.	V input	6A	2A	n.a.		X	X				1-4	n.a.	CE, UL	X	X	stick, side feed	plastic	153 x 50 x 23 mm	X	
LINEARdrive 720/D, DMX/DALI	LIN720D3	0,1%	LIN, LOG	cv	720W	4	12/24/48VDC	n.a.	n.a.	n.a.	V input	24A	6A	n.a.		X	X	X	X		1-4	1-4	CE, UL	X	X	stick, side feed	plastic	153 x 50 x 23 mm	X	
LINEARdrive 211/D, 0-10V	LIN211D1	0,1%	LIN, LOG	cv	200W	2	12/24/28VDC	n.a.	n.a.	n.a.	Vinput	8A	8A	n.a.		X					n.a.	n.a.	CE, UL		X	stick, side feed	plastic	153 x 50 x 23 mm	X	
LINEARdrive 210/D, DALI	LIN210D1	0,1%	LIN, LOG	cv	200W	2	12/24/28VDC	n.a.	n.a.	n.a.	V input	8A	8A	n.a.					X		n.a.	1	CE, UL		X	stick, side feed	plastic	153 x 50 x 23 mm	X	
LINEARdrive 220/D, DALI	LIN220D1	0,1%	LIN, LOG	cv	200W	2	12/24/28VDC	n.a.	n.a.	n.a.	V input	8A	8A	n.a.					X		n.a.	2	CE, UL		X	stick, side feed	plastic	153 x 50 x 23 mm	X	
LINEARdrive 212/D, DMX	LIN212D1	0,1%	LIN, SQU, LOG	cv	200W	2	12/24/28VDC	n.a.	n.a.	n.a.	V input	8A	8A	n.a.		X	X	X			1	n.a.	CE, UL		X	stick, side feed	plastic	153 x 50 x 23 mm	X	
LINEARdrive 222/D, DMX	LIN222D1	0,1%	LIN, SQU, LOG	cv	200W	2	12/24/28VDC	n.a.	n.a.	n.a.	V input	8A	8A	n.a.		X	X	X			2	n.a.	CE, UL		X	stick, side feed	plastic	153 x 50 x 23 mm	X	