

# instalight 3214





## Downlight



The particularly light-intense downlight offers wide light distribution and is thus ideally suited for broad illumination of high rooms. In addition, state-of-the-art reflector geometry allows the luminaire to vanish discreetly into the ceiling.





### Product features

- Visible housing sections powder-coated
- Operation on safety lighting systems saves additional lamps
- Simple installation through preterminated power supply units
- Integrated safety glass for an increased degree of protection
- Toolless mounting using spring technology





Overall size (mm)				Beam angle
H	ET	D	ED	
130	160	195	175	
130	160	195	175	
130	160	195	175	
130	160	195	175	

typ. Light colour (K)	typ. $\Phi_v$ (rated)	CRI	P (W)	$\eta_v$ (lm/W)	Dimmable / Interface	RAL	Optics	Weight (kg)	Article number	
	3000	3700 lm	>90	48	77	No / None	9016	Clear	1.4	<b>il 3214 A 930 00</b>
	3000	3700 lm	>90	48	77	Yes / DALI	9016	Clear	1.4	<b>il 3214 A 930 DA</b>
	4000	4700 lm	>80	48	98	No / None	9016	Clear	1.4	<b>il 3214 A 840 00</b>
	4000	4700 lm	>80	48	98	Yes / DALI	9016	Clear	1.4	<b>il 3214 A 840 DA</b>

### Technical data

<b>Rated voltage AC</b>	220 ... 240 V~	<b>Height (mm)</b>	130
<b>Mains frequency</b>	50 ... 60 Hz	<b>Installation depth (mm)</b>	160
<b>Rated voltage DC</b>	186 V ... 250 V=	<b>Degree of protection</b>	IP44
<b>Power consumption</b>	48 W	<b>Weight</b>	Approx. 1.4 kg
<b>Power factor</b>	0.90	<b>Housing material</b>	Aluminium
<b>Protection class</b>	II	<b>Ambient temperature</b>	-5 ... +35 °C
<b>Connection mode</b>	Screwless terminal	<b>Service life (L70/B50)</b>	50,000 h
<b>Efficiency class</b>	A+	<b>Installation diameter (mm)</b>	175
<b>External diameter (mm)</b>	194		