


instalight 3215





Downlight

The light-intense downlight offers particularly wide light distribution and is thus ideally suited for broad illumination of low to medium-height rooms.

Product features

- Visible housing sections powder-coated
- Operation on safety lighting systems saves additional lamps
- Simple installation through preterminated power supply units
- Softly dissipating light cone through special reflector surface
- Toolless mounting using spring technology





Overall size (mm)				Beam angle
H	ET	D	ED	
113	150	156	140	
113	150	156	140	69°
113	150	156	140	
113	150	156	140	69°

typ. Light colour (K)	typ. Φ_v (rated)	CRI	P (W)	η_v (lm/W)	Dimmable / Interface	RAL	Optics	Weight (kg)	Article number	
	3000	2300 lm	>90	30	77	No / None	9016	Clear	1.1	il 3215 A 930 00
	3000	2300 lm	>90	30	77	Yes / DALI	9016	Clear	1.1	il 3215 A 930 DA
	4000	2500 lm	>80	30	83	No / None	9016	Clear	1.1	il 3215 A 840 00
	4000	2500 lm	>80	30	83	Yes / DALI	9016	Clear	1.1	il 3215 A 840 DA

Technical data

Rated voltage AC	220 ... 240 V~	Height (mm)	113
Mains frequency	50 ... 60 Hz	Installation depth (mm)	150
Rated voltage DC	186 V ... 250 V=	Degree of protection	IP20
Power consumption	30 W	Weight	Approx. 1.1 kg
Power factor	0.90	Housing material	Aluminium
Protection class	II	Ambient temperature	-5 ... +35 °C
Connection mode	Screwless terminal	Service life (L80/B10)	50,000 h
Efficiency class	A+	Installation diameter (mm)	140
External diameter (mm)	156		