

instalight 3216



Downlight



The downlight, with medium-width radiation, is particularly suitable for atmospheric accentuation or general illumination of small to medium-sized rooms.

Product features

- Visible housing sections powder-coated
- Operation on safety lighting systems saves additional lamps
- Simple installation through preterminated power supply units
- Integrated safety glass for an increased degree of protection
- Toolless mounting using spring technology

IP44





Overall size (mm)				Beam angle
H	ET	D	ED	
125	150	111	95	
125	150	111	95	42°
125	150	111	95	
125	150	111	95	42°
125	150	111	95	
125	150	111	95	42°

typ. Light colour (K)	typ. Φ_v (rated)	CRI	P (W)	η_v (lm/W)	Dimmable / Interface	RAL	Optics	Weight (kg)	Article number	
	2700	1050 lm	>80	13	81	No / None	9016	Clear	0.7	il 3216 A 827 00
	2700	1050 lm	>80	13	81	Yes / DALI	9016	Clear	0.7	il 3216 A 827 DA
	3000	1050 lm	>80	13	81	No / None	9016	Clear	0.7	il 3216 A 930 00
	3000	1050 lm	>80	13	81	Yes / DALI	9016	Clear	0.7	il 3216 A 930 DA
	4000	1050 lm	>80	13	81	No / None	9016	Clear	0.7	il 3216 A 840 00
	4000	1050 lm	>80	13	81	Yes / DALI	9016	Clear	0.7	il 3216 A 840 DA

Technical data

Rated voltage AC	220 ... 240 V~	Height (mm)	125
Mains frequency	50 ... 60 Hz	Installation depth (mm)	150
Rated voltage DC	186 V ... 250 V=	Installation diameter (mm)	95
Power consumption	13 W	Degree of protection	IP44
Power factor	0.90	Weight	Approx. 0.7 kg
Protection class	II	Housing material	Aluminium
Connection mode	Screwless terminal	Ambient temperature	-5 ... +35 °C
Efficiency class	A+	Service life (L80/B10)	50,000 h
External diameter (mm)	111		