

instalight 3217






Downlight

The medium-width radiation downlight possesses a rotatable and swivellable reflector and is thus suitable for targeted accentuation. The choice of two output classes means that the luminaire can also be ideally matched to the room to be illuminated.

Product features

- Visible housing sections powder-coated
- Operation on safety lighting systems saves additional lamps
- Simple installation through preterminated power supply units
- Integrated safety glass for an increased degree of protection
- Rotatable and swivellable reflector for exact illumination
- Toolless mounting using spring technology





| Overall size (mm) | | | | Beam angle |
|-------------------|-----|-----|-----|------------|
| H | ET | D | ED | |
| 125 | 180 | 195 | 180 | |
| 125 | 180 | 195 | 180 | 33° |
| 125 | 180 | 195 | 180 | |
| 125 | 180 | 195 | 180 | 33° |
| 125 | 180 | 195 | 180 | |
| 125 | 180 | 195 | 180 | 33° |
| 125 | 180 | 195 | 180 | |
| 125 | 180 | 195 | 180 | 33° |

| typ. Light colour (K) | typ. Φ_v (rated) | CRI | P (W) | η_v (lm/W) | Dimmable / Interface | RAL | Optics | Weight (kg) | Article number | |
|-----------------------|-----------------------|---------|-------|-----------------|----------------------|------------|--------|-------------|----------------|----------------------------|
| | 3000 | 2500 lm | >90 | 30 | 83 | No / None | 9016 | Clear | 2.2 | il 3217 A1 930 00 |
| | 3000 | 2500 lm | >90 | 30 | 83 | Yes / DALI | 9016 | Clear | 2.2 | il 3217 A1 930 DA |
| | 4000 | 2600 lm | >80 | 30 | 87 | No / None | 9016 | Clear | 2.2 | il 3217 A1 840 00 |
| | 4000 | 2600 lm | >80 | 30 | 87 | Yes / DALI | 9016 | Clear | 2.2 | il 3217 A1 840 DA |
| | 3000 | 3700 lm | >90 | 47 | 79 | No / None | 9016 | Clear | 2.2 | il 3217 A1 930 S 00 |
| | 3000 | 3700 lm | >90 | 47 | 79 | Yes / DALI | 9016 | Clear | 2.2 | il 3217 A1 930 S DA |
| | 4000 | 4200 lm | >80 | 47 | 89 | No / None | 9016 | Clear | 2.2 | il 3217 A1 840 S 00 |
| | 4000 | 4200 lm | >80 | 47 | 89 | Yes / DALI | 9016 | Clear | 2.2 | il 3217 A1 840 S DA |

Technical data

| | | | |
|-------------------------------|--------------------|-----------------------------------|----------------|
| Rated voltage AC | 220 ... 240 V~ | Height (mm) | 125 |
| Mains frequency | 50 ... 60 Hz | Installation depth (mm) | 180 |
| Rated voltage DC | 186 V ... 250 V= | Installation diameter (mm) | 180 |
| Power consumption | 30 W / 47 W | Degree of protection | IP20 |
| Power factor | 0.90 | Weight | Approx. 2.2 kg |
| Protection class | II | Housing material | Aluminium |
| Connection mode | Screwless terminal | Ambient temperature | -5 ... +35 °C |
| Efficiency class | A+ | Service life (L80/B10) | 50,000 h |
| External diameter (mm) | 195 | | |