


LEDLUX LN linear Light insert





The linear light insert supplies high-quality, medium-intensity white light and can be integrated into the architecture in a modular fashion. In so doing, the light element stands out through its even light distribution and high light quality.

Main Features


- > Modular component system guarantees maximum design flexibility and scalability in the object
- > More than 250,000 product variants provide the right light for every idea
- > Weatherproof housing for use outdoors
- > Various abstract characteristics make focused illumination possible
- > Dimmable via PWM




Product Variations



120°



70°, CLEAR



70°, FRESNEL

	Optics	Optics dir.	Max. lumin. flux	Light colour
LL LN 830X (...) C070 (...)	Clear	70°	630 lm	3000 K
LL LN 840X (...) C070 (...)	Clear	70°	630 lm	4000 K
LL LN 827X (...) C070 (...)	Clear	70°	630 lm	2700 K
LL LN 840X (...) G070 (...)	Fresnel	70°	610 lm	4000 K
LL LN 830X (...) G070 (...)	Fresnel	70°	610 lm	3000 K
LL LN 827X (...) G070 (...)	Fresnel	70°	610 lm	2700 K
LL LN 840X (...) S120 (...)	Satined	120°	575 lm	4000 K
LL LN 830X (...) S120 (...)	Satined	120°	575 lm	3000 K
LL LN 827X (...) S120 (...)	Satined	120°	575 lm	2700 K

Specifications

Rated voltage DC	28 V SELV	Height	21 mm
Power consumption	7.2 W/m	Connection mode	See order code
Degree of protection	IP20/IP64 (see order code)	Cable length	See order code
Efficiency class	A+	Dimmable/Controllable	Yes
Protection class	III	Interface	Depending on the ballast used
Ambient temperature	-20 ... +45 °C	Housing material	Plastic
Storage/transport temperature	-20 ... +60 °C	Cover material	Plastic
Service life (L80/B10)	(@ 25 °C) 60,000 h	Glow-wire testing	850 °C
Length	253 ... 2286 mm	Weight	Approx. 0.2 kg/m
Width	20 mm	Impact strength	IK06

Accessories



Safety sleeve IP67
50900049



Supply unit 0-120 W / AM
58920027



SNT ELI 0-120 W
58916023



SNT ELI 0-57 W
58916030



SNT ELI 0-9 W Molex plug 3-pole
58910003



SNT ELI 0-110 W / 30 V
50930074



Flat clamp
81081700




High clamp
81081710



DMX-PWM converter
59701090



instalight Vario basic device
V2 GR 001



instalight Vario interface module PWM
V2 FM PW 001



Dimmbox
28105100