


instalight NoLimit 4033 High Power Accent light insert
Miniature light insert





The High Power Accent modules are perfectly suited for highlights and accents. With High Power Accent, the exact volume of light can be controlled by adjusting the number of modules employed. Each module is also adjustable, so that any alignment can also be precisely made.

Main Features


- > Light unit can be rotated variably to all sides and is easy to align exactly
- > Highest flexibility in design of planning to realisation
- > Tunable White (2700 K - 5000 K), free of artefacts and perfectly mixed from one optic




Product Variations




12° X 43°


































































14°



30°



43°

				Optics dir.	Max. lumin. flux	Light colour	LI	Housing colour
il4033_HA830X_B30_0041_CC_XX01				30°	255 lm	3000 K	6	RAL 9011 (Black)
il4033_HA827X_B30_0041_CC_XX01				30°	255 lm	2700 K	6	RAL 9011 (Black)
il4033_HA830X_W30_0041_CC_XX01				30°	265 lm	3000 K	6	RAL 9016 (traffic white)
il4033_HA827X_W30_0041_CC_XX01				30°	265 lm	2700 K	6	RAL 9016 (traffic white)
il4033_HA840X_B30_0041_CC_XX01				30°	275 lm	4000 K	6	RAL 9011 (Black)
il4033_HA840X_W30_0041_CC_XX01				30°	285 lm	4000 K	6	RAL 9016 (traffic white)
il4033_HA2750_B43_0041_CC_XX01				43°	210 lm	2700 ... 5000 K (TW)	5	RAL 9011 (Black)
il4033_HA2750_W43_0041_CC_XX01				43°	220 lm	2700 ... 5000 K (TW)	5	RAL 9016 (traffic white)
il4033_HA827X_B14_0041_CC_XX01				14°	270 lm	2700 K	6	RAL 9011 (Black)
il4033_HA830X_B14_0041_CC_XX01				14°	270 lm	3000 K	6	RAL 9011 (Black)
il4033_HA830X_W14_0041_CC_XX01				14°	280 lm	3000 K	6	RAL 9016 (traffic white)
il4033_HA827X_W14_0041_CC_XX01				14°	280 lm	2700 K	6	RAL 9016 (traffic white)
il4033_HA840X_B14_0041_CC_XX01				14°	290 lm	4000 K	6	RAL 9011 (Black)
il4033_HA840X_W14_0041_CC_XX01				14°	300 lm	4000 K	6	RAL 9016 (traffic white)
il4033_HA827X_B5C_0041_CC_XX01				12° X 43°	255 lm	2700 K	6	RAL 9011 (Black)
il4033_HA830X_B5C_0041_CC_XX01				12° X 43°	255 lm	3000 K	6	RAL 9011 (Black)
il4033_HA830X_W5C_0041_CC_XX01				12° X 43°	265 lm	3000 K	6	RAL 9016 (traffic white)
il4033_HA827X_W5C_0041_CC_XX01				12° X 43°	265 lm	2700 K	6	RAL 9016 (traffic white)
il4033_HA840X_B5C_0041_CC_XX01				12° X 43°	275 lm	4000 K	6	RAL 9011 (Black)
il4033_HA840X_W5C_0041_CC_XX01				12° X 43°	285 lm	4000 K	6	RAL 9016 (traffic white)

Specifications

Lifecycle Status	Active	Width (B)	41 mm
Power consumption	3 W	Height (H)	54 mm
Degree of protection	IP20	Connection mode	Plug connector
Protection class	III	Dimmable/Controllable	Yes
Optics	Clear	Interface	depending on the driver
Ambient temperature	5 °C ... 25 °C ... 45 °C	Housing material	Aluminium
Service life (L80/B10)	60,000 h (at 25°C)	Weight	0.05 kg
Length (L)	41 mm	Nominal current	900 mA

Accessories



Cable bracket set (20 pieces)
IL4033_ZM_K_001



instalight NoLimit 4033 profile cover



Short circuit plug 4p
IL4033_KSS



Extension cable routing for Mid Power Linear and High Power modules



Extension cable 4p dt8



Short-circuit connector dt8
IL4033_Q4P_KSS



il4033 Control Gear CC intra-profile TW DALI DT8



il4033 Control Gear CC external



il4033 Control Gear CC intra-profile



il4033 Control Gear CC external TW DALI DT8