


instalight 3065 R 00
Cubic compact spot






The miniature spot, with its high light output, can primarily show its benefits in targeted accenting. Precisely directed white light, an integrated power supply module and the ultra-compact design turn this luminaire into the ideal lighting tool for delicate presentations on buildings, as well as in parks and gardens.

Main Features


- > Minimum installation and planning effort due to direct access to main voltage
- > Positive locking cover disk prevents dirt adhesion
- > Mounting bracket can be removed for easy and comfortable assembly




Product Variations










10°



30°



54°

		Optics dir.	Max. lumin. flux	Light colour
il 3065R A 30 830 A1 0230 00		30°	860 lm	3000 K
il 3065R A 30 840 A1 0230 00		30°	910 lm	4000 K
il 3065R A 10 830 A1 0230 00		10°	940 lm	3000 K
il 3065R A 10 840 A1 0230 00		10°	980 lm	4000 K
il 3065R A 54 830 A1 0230 00		54°	820 lm	3000 K
il 3065R A 54 840 A1 0230 00		54°	860 lm	4000 K

Specifications

Lifecycle Status	Active
Beam Geometry	rotationally symmetrical
Light distribution	symmetrical
Rated voltage AC	230 / 240 V
Mains frequency	50 / 60 Hz
Power consumption	9.5 W
Power factor	0.6
Degree of protection	IP67
Efficiency class	A+
Protection class	I
Optics	Clear
Colour rendition Ra	85
Ambient temperature	-20 ... +35 °C

Storage/transport temperature	-25 ... +85 °C
Service life (L80/B10)	60,000 h
Length (L)	110 mm
Width (B)	105 mm
Height (H)	167 mm
Connection mode	Free cable ends
Cable length	2000 mm
Dimmable/Controllable	No
Interface	No
Housing colour	Silver grey
Housing material	Aluminium
Cover material	Tempered glass
Weight	approx. 1.5 kg
Impact strength	IK10 / IK05