

## DMX Repeater

The Pharos RDM (Remote Device Management) is a 4 port DMX512 Splitter compatible with the RDM standard to provide DMX output to luminaires and other devices.



## RDM Features



### RDM

Supports the Remote Device Management protocol (ANSI E1.20) allowing devices connected to any of the four outputs to communicate back to a Controller over the DMX link.



### Installer Friendly

Made for permanent installation, with installer-friendly connectors and easy DIN rail mounting.



### Four Outputs

Repeats a DMX signal to 4 outputs, each allowing for 32 DMX devices to be connected.



### Reliable

Hardware and firmware are self-sufficient, so no PC needs to be left on site. Rugged, compact unit designed for 24/7 operation and reliability.



### Isolated

Opto-isolated input and through connection for daisy-chaining the DMX connection.




## Interfaces

<b>DMX/RDM input</b>	DMX512 port, RDM compatible *
<b>DMX/RDM thru</b>	DMX512 port, RDM compatible *
<b>DMX/RDM outputs</b>	Four DMX512 ports, RDM compatible *

\* Install-friendly 0.200" (5.08mm) plug in rising clamp connectors (included)

## Specifications

<b>Power</b>	9-48V DC (4W typical)
<b>Temperature</b>	0°C to 50°C (32°F to 122°F)
<b>Humidity</b>	10-50% relative, non-condensing
<b>Ingress</b>	IP40
<b>Physical</b>	6 unit wide DIN rail mounting enclosure (DIN43880 / EN60715 (35/7.5 rail)) 0.5 kg (1.1 lbs)
<b>Shipping</b>	20 x 15 x 12 cm (8" x 6" x 5") 0.7 kg (1.6 lbs)



## Order Code & Variants

<b>RDM</b>	Designer DMX/RDM Splitter (4+1 Port: 1 in, 1 thru, 4 out)
------------	---

## Warranty & Certifications

<b>Warranty</b>	5 years
<b>Certifications</b>	CE compliant, UKCA compliant, ETL/cETL listed.

